

A

DOCKET NO. PF02024NA
Express Mail Label # EL626111504US

Box: Patent Application

Assistant Commissioner for Patents
Washington, D.C. 20231

Transmitted herewith for filing under 37 CFR §1.53(b) is a Nonprovisional:
New Application XX; Continuation _____, Division, _____ or Continuation in Part (CIP) _____
of prior US application S/N _____, filed on _____.

Title: **CONTEXTUALLY AWARE NETWORK ANNOUNCEMENTS OF PEOPLE**

For: **Eric R. Schorman and John D. Reed**

Enclosed are the following documents:

- ☒ Transmittal Letter to PTO;
☒ PrintEFS Inventor Information Sheet;
☒ 3 sheet(s) of drawings and 16 page(s) of specification and claims;
☒ Oath or Declaration Combined with Power of Attorney (2 pages).
☒ Newly Executed (original or copy).
_____ Copy from a prior application (if this is a Continuation/Division).
_____ signed statement deleting named inventor(s) in prior application if
_____ this is a Continuation/Division (see 37 CFR § 1.63(d) and §1.33(b).
_____ Please abandon the prior application identified above as of the filing date
granted to the present Continuation/Division application.
_____ Enclosed is a certified copy of a _____ (non-US) application S/N _____
having a filing date of __, and foreign priority to this non-US application for
the present application is hereby claimed under 35 USC §119.
☒ Assignment Transmittal and Assignment to MOTOROLA, INC.
_____ An Information Disclosure Statement and PTO 1449 with references attached.
_____ Preliminary Amendment.
☒ Return postcard.

CLAIMS AS FILED

FOR	NUMBER FILED	NUMBER EXTRA	RATE	FEE
TOTAL CLAIMS	27-20		X \$18.00	126.00
INDEPENDENT CLAIMS	3-3		X \$78.00	
MULTIPLE DEPENDENT CLAIM(S)			\$260.00	
ASSIGNMENT DOCUMENT			\$40.00	\$40.00
BASIC FEE				\$690.00
TOTAL FILING FEE				\$856.00

Please charge my deposit account no. **50-0280** in the amount of **\$856.00**.

The Commissioner is hereby authorized to charge any fees under 37 CFR §1.16 and 1.17 which may be required during the entire pendency of this application, or credit any overpayment, to deposit account No. **50-0280**.

Date _____

7-31-00

Charles W. Bethards
Charles W. Bethards Reg. No. 36,453
MOTOROLA, INC.
Intellectual Property Department - MS E230
5401 North Beach Street
Fort Worth, Texas 76137
Tel: (817) 245-2571; Fax: (817) 245-2137

Express Mail Label No. EL626111504US

INVENTOR INFORMATION

Inventor One Given Name:: ERIC R
Family Name:: SCHORMAN
Postal Address Line One:: 1304 WEDGLEA DRIVE
City:: BEDFORD
State or Province:: TX
Country:: USA
Postal or Zip Code:: 76021
Citizenship Country:: USA
Inventor Two Given Name:: JOHN D
Family Name:: REED
Postal Address Line One:: 1101 BRIARCLIFF DRIVE
City:: ARLINGTON
State or Province:: TX
Country:: USA
Postal or Zip Code:: 76012
Citizenship Country:: USA

CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 23447
Name Line One:: MOTOROLA, INC.
Name Line Two:: IP LAW DEPT. - MAIL STOP E230
Address Line One:: 5401 N. BEACH STREET
City:: FORT WORTH
State or Province:: TX
Country:: USA
Postal or Zip Code:: 76137
Telephone One:: 817-245-2911
Fax One:: 817-245-2137
Electronic Mail One:: FTD050C@email.mot.com

APPLICATION INFORMATION

Title Line One:: CONTEXTUALLY AWARE NETWORK ANNOUNCEMENTS
Title Line Two:: OF PEOPLE
Total Drawing Sheets:: 4
Formal Drawings?: Yes
Application Type:: Utility
Docket Number:: PF02024NA
Secrecy Order in Parent Appl.?: No

Source:: PrintEFS Version 1.0.1

CONTEXTUALLY AWARE NETWORK ANNOUNCEMENTS OF PEOPLE

Field of the Invention

5 The invention relates generally to a system for making contextually aware network announcements of people. More particularly, the invention relates to an apparatus and method for announcing the presence of a member of an ad hoc network to other members of the ad hoc network.

Background of the Invention

10 Social or business gatherings are sometimes uncomfortable for people who cannot remember names or other information about people they meet at those gatherings. Personal organizers allow a user to manually access such information
15 through a keyboard or touch screen.

20 Certain devices, such as cellular telephones, personal digital assistants (PDAs), palm top computers, laptop computers, and other such devices, may have the ability to communicate with each other via a wireless interface. For example, a cellular telephone may have the ability to communicate wirelessly with a laptop computer via a Bluetooth interface or an infrared interface. Such an interface may allow the transmission of data between the cellular telephone and the laptop computer.

Brief Description of the Drawings

Fig. 1 is a representation of an ad hoc network.

Fig. 2 is a representation of an ad hoc network with a new member.

5 Fig. 3 is a block diagram of a personal communicator according to the present invention.

Fig. 4 is a block diagram of a personal communicator according to the present invention, illustrating a variety of output devices.

Figs. 5-8 are illustrations of a queue.

10 Fig. 9 is an illustration of a personal communicator showing a queue and devices for selecting items on the queue.

Detailed Description of the Preferred Embodiments

Information regarding a person is communicated through an ad hoc network of personal communicators, such as cellular telephones or PDAs, to an announcing personal communicator. The announcing personal communicator accesses a database of information regarding the person to be announced and provides a subset of that information to the user.

Depicted in Fig. 1 is an ad hoc network of personal communicators that provides wireless communications between its members 102, 104, 106 and 108. The wireless communications may be any form of communication that accomplishes the purposes described below, including cellular communications, Bluetooth communications or optical communications. In the ad hoc network illustrated in Fig. 1, personal communicators may move in and out of the network as they move in and out of communications range of each other.

A scenario in which such an ad hoc network might be created is a social gathering, such as a party. At the beginning of the party, for example, only one personal communicator 102 may be present. The personal communicator 102 may be a cellular telephone carried by the host of the party. After the party begins, a guest carrying a personal communicator 104, which may be a PDA, arrives at the party. When the two personal communicators 102 and 104 establish contact with each other, the ad hoc network consists of personal communicator 102 and personal communicator 104. Subsequently, other guests arrive carrying personal communicators 106 and 108. When personal communicators 106 and 108 establish contact with the other personal communicators 102 and 104 and each other, the ad hoc network expands to include those personal communicators 106 and 108. The personal communicators 102, 104, 106 and 108 may transfer information among themselves with or without the intervention of their users.

The information transferred may include the identity of the person carrying the personal communicator. If a new person carrying a personal communicator 202 joins the ad hoc network, as shown in Fig. 2, an identification of the new person will be transmitted from the personal communicator 202 through personal communicators 104 and 106 to personal communicator 108. Any one of communicators 104, 106, or 108 has sufficient information, based on the communication from personal communicator 202, to provide an alert to their respective owners of the presence of the person carrying personal communicator

202. The personal communicator 202 may communicate directly with personal communicators 106 and 108 or through relays as shown in Fig. 2.

Personal communicators 104, 106, and 108 may also announce the presence of the other's owners. For example, personal communicator 108 may also
5 announce the presence of the owners of personal communicators 104 and 106.

Each of the personal communicators may limit its announcements to only those personal communicators within a certain proximity of that personal communicator. Proximity may be determined by measuring the signal strength of the received signal, by measuring the number of "hops" that the signal had to
10 make between the originating personal communicator and the receiving personal communicator, or any other proximity measuring technique. For example, if personal communicator 202 communicates directly with personal communicator 108, personal communicator 108 may measure the signal strength of the signal produced by personal communicator 202 and determine proximity by comparing
15 the measured signal strength to a predetermined threshold.

Alternatively, if the communication between personal communicator 202 and personal communicator 108 is by relay through personal communicators 104 and 106, as shown in Fig. 2, personal communicator 108 may decide that personal communicator 202 is not proximate to personal communicator 108 because of the
20 number of hops that the communication had to make (i.e., from personal communicator 202 to personal communicator 104, from personal communicator 104 to personal communicator 106, and from personal communicator 106 to personal communicator 108). The number of hops required to make a personal communicator not proximate to another personal communicator may be a variable
25 that could be set globally or within each personal communicator.

To accomplish the functions described above, the personal communicators have the block diagram illustrated in Fig. 3. An ad hoc network interface 302, such as a Bluetooth transceiver, provides an interface between the ad hoc network and a processor 304. The processor 304 may be a processor normally associated
30 with the primary function of the personal communicator. For example, in a cellular telephone, the processor 304 may be associated with the cellular telephone function. Alternatively, the processor may be dedicated to the functions described herein.

The processor 304 is programmed to retrieve communications from the ad
35 hoc network interface 302, which may include communications from other personal communicators that are members of the ad hoc network. Such communications may include the identity of the other members of the ad hoc

network. The processor 304 is programmed to retrieve information from a database 306 regarding the member or members identified in the communications. The database 306 may include such information as the relationship of the owner of the receiving personal communicator to the owner of the sending personal communicator, the job title of the owner of the sending personal communicator, the date and time of the most recent or next scheduled meeting between the two parties, assignments from the sending party to the receiving party, or other similar information. The processor 304 sorts the information retrieved from the database 306, and selects portions of it to display on an output device 308. The selections may be based on commands input by the user.

The information may be stored in the database 306 in a variety of ways. A user may input commands and data through an input device 310 to the processor 304, which places the data in a proper format for storage in the database 306. The input device 310 can be a traditional keyboard, a collapsible keyboard, a touch screen, a voice input, or any other device capable of providing information appropriate for storage in the database 306.

Further, the processor 304 may extract data received in communications from other personal communicators and store it in the database 306. For example, a personal communicator that is a member of the network may transmit an communication containing an "electronic business card," which includes basic information about the owner of the transmitting personal communicator, such as name, business affiliation, address, telephone number, email address, etc. If the receiving personal communicator does not already have a record built for that person in database 306, it may build one with the information in the electronic business card. If a record already exists, but the electronic business card contains additional information, the processor 304 may add the additional information to the record in the database 306.

Still more information about the owner of the transmitting personal communicator may be maintained in a database that is external to the receiving personal communicator. In this case, database 306 may be considered a distributed database, in that portions of its data are stored in various physical locations. For example, basic information about a set of people may be maintained in a portion of the database 306 stored on the personal communicator. Still more information about the set of people, or about other people, may be stored on a computer, accessible to the personal communicator wirelessly or through a network, or on another personal communicator accessible via the ad hoc network. When such information is retrieved from the computer or from another

personal communicator some or all of it may be stored in the database 306 on the personal communicator.

The communications between the personal communicators may include a link representing an address where additional information regarding the owner of the transmitting personal communicator may be stored. The receiving personal communicator may follow the link to the address, extract some or all of the stored information and store it in the database 306.

The output device 308 can take a variety of forms, as illustrated in Fig. 4. The output device 308 may be a display screen 402. In Fig. 4, the display screen is shown displaying information about Dr. John Doe, the president of Customer.com. The owner of the personal communicator illustrated in Fig. 4 has a white paper due to Dr. Doe "next week" and a meeting "next Tuesday." Such a visual display may be accompanied by a vibration of the personal communicator, as indicated by the marks 404 in Fig. 4.

A visual display may be made as a "heads up" display on a pair of glasses 406.

Alternatively, the announcement may be made audibly through an earpiece 408.

The output device 308 could be adapted to provide information to handicapped people. For example, the output device 308 could be a tactile output device for a person who is visually impaired. Further, the announcement can be made through any output device capable of conveying the information retrieved from the database.

The personal communicator illustrated in Fig. 4 also includes two control buttons 410 and 412.

In addition to the information described above, communications between personal communicators may include audio or graphic data, such as photographic images, representations of logos, audio recordings, etc., or links to addresses where such information is stored. The receiving personal communicator may be configured to receive such data and store it in the database 306 and subsequently display it or otherwise announce it on the output device 308.

The database may also contain the date and time when a communication was received from another personal communicator. Such information could be stored in the database 306 along with the proximity information. Location information, derived in a conventional manner (e.g. GPS), could be included in the communication and stored in the database 306. The location information could be

for the receiving personal communicator or the transmitting personal communicator.

There may be situations, such as those shown in Fig. 2, in which a personal communicator, such as personal communicator 108, will receive more than one announcement. In such cases, the announcements are placed in a queue, as shown in Fig. 5. Fig. 5 illustrates five announcements queued in the order in which they were received by the announcing personal communicator. The personal communicator reports the announcements in the order in which they are listed in the queue, from top to bottom. Thus, announcement 1 will be announced first, followed by announcement 2, and so on. In Fig. 6, a sixth announcement has been received and added to the bottom of the queue.

The personal communicator also includes the ability to assign priorities to announcements. For example, if an announcement is received from a person to whom, for example, the owner of the announcing personal communicator is obligated or with whom the owner has a special relationship (such as supervisor), the personal communicator may allow that announcement to be placed in the queue somewhere above the bottom. For example, in Fig. 7, announcement 7 has been received and determined to be of sufficient priority that it is added to the top of the queue rather than the bottom.

In some situations, it may be important to list the announcements in the order of proximity to the announcing personal communicator, where proximity is determined using one of the methods described above. Further, it may be desired not to display announcements from personal communicators outside a proximity limit. In Fig. 8, for example, the announcements are listed in order of priority, and in order of proximity to the announcing personal communicator, with some of the announcements being left off the list entirely. Thus, announcement 7 is at the top of the queue because of its priority. Announcement 2 is second because of the proximity of the associated personal communicator to the announcing personal communicator. Announcements 3, 4 and 6 have been left off the queue entirely because of their distance from the announcing personal communicator.

The queue may be shown on the display screen of the personal communicator, as shown in Fig. 9. In this representation, priority announcements are shown with stars 902 to indicate to the user the priority of the announcement. The user can highlight a particular announcement, as indicated by the box 904, and select it to display the associated information, using the select button 906. Cursor control buttons 908 and 910 allow the selection box 904 to be moved. Another button 912 provides additional controls.

After a period of time, the database 306 will contain a record of events associated with the owner of the personal communicator containing the database 306, including, for example, the date and time of a communication, the location of the transmitting personal communicator, the location of the receiving personal communicator, and the determination of proximity between the two personal communicators. The processor 304 would filter the communications in real time and announce on output device 308 only communications from personal communicators meeting priority and proximity requirements, as discussed above. The processor would store in the database 306 all, or some subset, of the received communications for later analysis. Subsequently, the data in the database could be retrieved in time order, or in some other meaningful order, for analysis. A different proximity filter than that applied during real time announcement of data could be applied to the data during later analysis, allowing data not previously reviewed to be examined. Further, the database could be searched for additional information, such as, for example, whether a particular person attended a meeting.

The foregoing describes preferred embodiments of the invention and is given by way of example only. The invention is not limited to any of the specific features described herein, but includes all variations thereof, within the scope of the appended claims.

Claims

What is claimed is:

1. A context-sensitive data announcing device comprising

an ad hoc network interface configured to receive one or more announcements
5 identifying one or more members of an ad hoc network;

a database comprising information regarding one or more of the members;

a processor configured to extract the information regarding the one or more
members from the database using the identifying announcement; and

an output for outputting the information regarding the one or more members.
- 10 2. The device of claim 1 further comprising

a queue for storing the information regarding the one or more members.
3. The device of claim 2 wherein

the queue couples the information regarding the one or more members to the
output in the order the announcements were received.
- 15 4. The device of claim 2 wherein

the information regarding an urgent member comprises an urgent designation;
and

the queue is configured to couple the information regarding the urgent member to the output before the information regarding at least some of the one or more members.

5. The device of claim 1 wherein

5 the processor is configured to extract the information regarding the one or more members that are proximate to the device.

6. The device of claim 5 wherein

the processor is configured to determine the proximity of the one or more members using a signal strength provided by the network interface.

10 7. The device of claim 5 wherein

the processor is configured to determine the proximity of a member using the number of hops among members the announcement associated with the member made before being received by the ad hoc network interface.

8. The device of claim 1 wherein

15 the ad hoc network interface uses one of radio frequency communications, optical communications, or wired communications.

9. The device of claim 1 wherein

the output comprises one of a vibrating mechanism, an audio output, or a visual output.

10. A method for an announcing member of an ad hoc network to announce the presence of one or more members of the ad hoc network, the method
5 comprising

receiving an identifying announcement from one or more members of the ad hoc network;

accessing a database using the one or more identifying announcements to retrieve information regarding each of the one or more members of the ad
10 hoc network from which an announcement was received; and

outputting the information.

11. The method of claim 10 further comprising
queuing the identifying announcements.

12. The method of claim 11 wherein queuing comprises

15 queuing the identifying announcements in the order received.

13. The method of claim 11 wherein queuing comprises

raising an urgent identifying announcement to a top of the queue.

14. The method of claim 10 further comprising

determining the proximity to the announcing member of each of the members of the ad hoc network from which the announcing member received an announcement; and

5 outputting comprises outputting only the identifying data for members of the ad hoc network that are proximate to the announcing member.

15. The method of claim 14 wherein the announcements hop among members of the ad hoc network in order to reach the announcing member and wherein

determining the proximity comprises counting the hops an announcement
10 made before reaching the announcing member.

16. The method of claim 14 further comprising

measuring the signal strength of each received identifying announcement; and wherein

determining the proximity comprises comparing the signal strength of each
15 received identifying announcement to a threshold.

17. The method of claim 10 further comprising

building the database.

18. The method of claim 17 wherein building the database comprises

extracting new information from the one or more identifying announcements;

5 and

storing the new information in the database.

19. The method of claim 17 wherein building the database comprises

retrieving new information from a database external to the announcing
member; and

10 storing the new information in the database.

20. A system for identifying members of an ad hoc network, the system
comprising

15 communicators, associated with one or more source members and a display
member, for communicating announcements regarding the source
members between the source members and the display member;

a database comprising information regarding the source members;

a processor configured to access the database using the announcements to
produce accessed information; and

an output associated with a display member for outputting the accessed information.

21. The system of claim 20 wherein

the processor is configured to access the database for only those source members that are proximate to the display member.

22. The system of claim 21 wherein

an announcement passes through zero or more communicators as it travels from the source members to the display member;

the processor is configured to determine the proximity of a source member to the display member based on the number of communicators the announcement passed through between the source member and the display member.

23. The system of claim 21 further comprising

one or more signals for carrying the announcements between the source members and the display member;

a signal strength measurer associated with the display member, the signal strength measurer producing a signal strength for each signal received from a source member; and wherein

the processor is configured to determine the proximity of the source members to the display member using the respective signal strengths.

24. The system of claim 20 wherein

the output displays the accessed information for the source members in the order that the announcements were received from the respective source members.

5 25. The system of claim 20 wherein

the accessed information for each source member has an associated urgency, the urgency having an order; and

the output displays the accessed information for the source members in the order of urgency.

10 26. The system of claim 20 wherein

the processor is associated with the display member.



27. The system of claim 20 wherein

the database is associated with the display member.

CONTEXTUALLY AWARE NETWORK ANNOUNCEMENTS OF PEOPLE

Abstract of the Disclosure

A context sensitive data announcing device includes an ad hoc network interface configured to receive one or more announcements identifying one or more members of an ad hoc network. The device includes a database which contains information regarding the one or more members of the ad hoc network. A processor is configured to extract the information regarding the one or more members from the database using the identifying announcements. The device includes an output for displaying the information regarding the one or more members.

**FIG. 1****FIG. 2**




FIG. 3




FIG. 4

ANNOUNCEMENT 1
ANNOUNCEMENT 2
ANNOUNCEMENT 3
ANNOUNCEMENT 4
ANNOUNCEMENT 5

FIG. 5

ANNOUNCEMENT 1
ANNOUNCEMENT 2
ANNOUNCEMENT 3
ANNOUNCEMENT 4
ANNOUNCEMENT 5
ANNOUNCEMENT 6

FIG. 6


ANNOUNCEMENT 7
ANNOUNCEMENT 1
ANNOUNCEMENT 2
ANNOUNCEMENT 3
ANNOUNCEMENT 4
ANNOUNCEMENT 5
ANNOUNCEMENT 6

FIG. 7

ANNOUNCEMENT 7
ANNOUNCEMENT 2
ANNOUNCEMENT 1
ANNOUNCEMENT 5

FIG. 8

FIG. 9



**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

Attorney Docket **PF2024NA**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **CONTEXTUALLY AWARE NETWORK ANNOUNCEMENTS OF PEOPLE** the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as Application No. _____
and was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

☐ Yes ☐ No

(Number) (County) (Day/Month/Year Filed)

☐ Yes ☐ No

(Number) (County) (Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

(Application Number) (Filing Date)

(Application Number) (Filing Date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §12, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)
(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Charles W. Bethards, Esq.
Motorola, Inc.
5401 N. Beach Street, Mail Stop E230
Fort Worth, Texas 76133
Direct Telephone Calls to: (817) 245-2571

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST INVENTOR Schorman, Eric R.	INVENTOR'S SIGNATURE <i>Eric R. Schorman</i>	DATE: 07/31/00
RESIDENCE: 1304 Wedglea Drive, Bedford, TX 76021, USA		CITIZENSHIP: USA
POST OFFICE ADDRESS Same as above		

FULL NAME OF SECOND INVENTOR Reed, John D.	INVENTOR'S SIGNATURE <i>John D. Reed</i>	DATE: 7-31-00
RESIDENCE: 1101 Briarcliff Drive, Arlington, TX 76012 USA		CITIZENSHIP: USA
POST OFFICE ADDRESS Same as above		